



MOUNTING HUB - CAST ZINC WITH 1/2-14 OR 3/4-14 N.P.T. THREADS TO ACCEPT STEM, OR CORD STRAIN RELIEF

TWO PIECE FRONT WIRING HEAVY-DUTY MEDIUM BASE PORCELAIN LAMPHOLDER WITH SPRING LOADED CENTER CONTACT AND LAMP GRIP NICKEL PLATED SCREW SHELL

LAMP TYPES: A, G, PS, R AND PAR TYPES 200 WATTS MAXIMUM A-19 SHOWN

PRECISION SPUN ALUMINUM REFLECTOR WITH ELECTROSTATICALLY APPLIED AND THERMALLY CURED POLYESTER POWDER COAT FINISH - WHITE STANDARD

TURNT IN BOTTOM BEAD ADDS STRENGTH AND PREVENTS THE COLLECTION OF DIRT

 LISTED FOR WET LOCATIONS  
APPROVED FOR CANADIAN USE

*RLM STANDARD DOME REFLECTOR No. 516*

**DRAWING NUMBER CAD-1410A**

Drawn by:	Date: 06-21-96	Drawing Units: INCHES	Scale: QUARTER
-----------	-------------------	--------------------------	-------------------

**THE SPERO ELECTRIC CORPORATION**

1790 MILLER PARKWAY STREETSBORO, OHIO 44241  
PHONE: (330) 995-3050 FAX: (330) 995-3051