



MOUNTING HUB - CAST ZINC WITH 1/2-14 OR 3/4-14 N.P.T. THREADS TO ACCEPT STEM, OR CORD STRAIN RELIEF

TWO PIECE FRONT WIRING HEAVY-DUTY MEDIUM BASE PORCELAIN LAMPHOLDER WITH SPRING LOADED CENTER CONTACT AND LAMP GRIP NICKEL PLATED SCREW SHELL

LAMP TYPES: A, G, PS, R AND PAR TYPES 500 WATTS MAXIMUM A-23 SHOWN MOGUL BASE UPON REQUEST

PRECISION SPUN ALUMINUM REFLECTOR WITH ELECTROSTATICALLY APPLIED AND THERMALLY CURED POLYESTER POWDER COAT FINISH - WHITE STANDARD

TURND IN BOTTOM BEAD ADDS STRENGTH AND PREVENTS THE COLLECTION OF DIRT



LISTED FOR WET LOCATIONS
APPROVED FOR CANADIAN USE

RLM STANDARD DOME REFLECTOR NO. 518

DRAWING NUMBER CAD-1412

Drawn by:	Date: 08-30-96	Drawing Units: INCHES	Scale: QUARTER
-----------	-------------------	--------------------------	-------------------

THE SPERO ELECTRIC CORPORATION

1790 MILLER PARKWAY STREETSBORO, OHIO 44241
PHONE: (330) 995-3050 FAX: (330) 995-3051